13.0 x 0.5mm thick galvanised steel band with buckle, or alternative approved by the Engineer, on all posts $_{\mbox{\scriptsize N}}$ 2850 max 38-11-Ω

TYPICAL CONSTRUCTION DETAILS - MORTICED POST AND FIVE RAIL FENCING

BS REF	MAIN POSTS LENGTH SECTION	PRICK POSTS LENGTH SECTION	NUMBER OF RAILS	HEIGHT TO TOP OF TOP RAIL	SPACING BETWEEN RAILS (FROM TOP)	VALUE OF D
-	2400* 75 x 150	1850 38 x 87	5	1300	250-250-140-125-100	1000

* The value can be reduced by 300 if posts are concreted in.



1. For Notes see Drg No SD/3/16A



©Crown copyright 2007. All rights reserved. Use of this image is limited to viewing on-line and printing one copy. Leicestershire County Council 400/1971



TRANSPORTATION AND

WASTE MANAGEMENT

STANDARD DRAWING

FENCING

POST AND FIVE RAIL FENCING

DRAWING NUMBER		:			
SD/3/18 SEF		PTEMBER 2002			
AUTOCAD REF		SCALE			
K:\GENERAL\D9997STDDRG\SD317					
		NOT TO SCALE	Rev	Date	Notes on Revision