



- NOTES:**
1. All dimensions are in millimetres unless otherwise stated.
 2. Softwood to be graded and pre-treated to meet BS 8417. All timber to have Forest Stewardship Council (FSC) Certification.
 3. Deck beams to be bolted to 'T' Section using 12mm diameter 'studding' bolts with nuts and washers bothends, cut off to length, burred to prevent undoing and ends painted with metal paint.
 4. This is drawing for decks of 6 - 9m only. For decks under 6m see Drg No SD/FP/16A. For further details of 'T' sections see Drg No SD/FP/18.
 5. Standard 'T' section precast concrete bank seat to be located in pre-dug hole and secured in ST3 concrete. Rapid set cement may be used.
 6. Treads (900mm x 300mm x 50mm) fixed with 4" galvanised (round) nails (oblique) 4 per tread.
 7. Railings to be galvanised steel tubing 48.3mm diameter (size 8) 'Kee Klamp' standard fittings (or suitable alternative) with galvanised finish to be used where joints or end fixings required. Railing height to be 750 - 900mm above bridge deck.

©Crown copyright 2014. All rights reserved. Use of this image is limited to viewing on-line and printing one copy. Leicestershire County Council. 100019271.

DRAWING NUMBER	DATE			
SD/FP/17^A	MARCH 2015			
AUTOCAD REF	SCALE			
K:\GENERAL\ID9997\STDDRG\	NOT TO SCALE	A	AUGUST 2015	Title and notes 2, 4 and 7 amended
		Rev	Date	Notes on Revision